



- NOTES:
1. ALL DIMENSIONS IN mm.
 2. ALL MOULDINGS TO BE FREE OF BURRS, FLASH AND SINK MARKS.]
MOULDINGS TO BE FREE OF DISTORTIONS AND TWISTS.
 3. PROCESS - INJECTION MOULDED.
 4. MATERIAL - GLASS FILLED NYLON.
 5. COLOUR - BLACK (PANTONE REF. : 900).
 6. GENERAL TOLERANCES = +0.25mm - -0.25mm.
 7. GENERAL WALL THICKNESS 2mm (U.O.S)
 8. DRAFT TAPERS = 0.5 DEGREES (U.O.S)
 9. SURFACE FINISH - REFER TO SURFACE FINISH TABLE.
 10. BREAK RADII - 0.5mm (U.O.S).

SURFACE FINISH TABLE	
SYMBOL	DESCRIPTION
	HIGHLY POLISHED Ra = 0.5 MICRONS
	SPARK ERODED REF. CHARMILLES 33

3	A	02/11/07	DIMENSIONING	JH		
2	A	01/10/07	DIMENSIONING	JH		
1	-	17/09/07	FOR DISCUSSION PURPOSE ONLY	JH		
ISSUE	CHNG	DATE	DESCRIPTION	DRAWN	CHECKED	APPROVED
<div><div>EDGE™</div><div>DESIGN DEVELOPEMENT</div><div>083 928 9240</div><div>JASOMMARCHOFFMAN@GMAIL.CO.ZA</div></div>				CLIENT NAME :		
				CLIENT CONTACT :		
				CLIENT DRWNG NO. :		
PROJECT : GAS STOVE			TITLE : CONTROLL KNOB INDICATOR			
		SCALE 2:1 (UOS)	SHEET: 1 OF 1	DRAWING NO. : UJ/07/03/03/006		
DO NOT CHANGE BY HAND			COPYRIGHT JASON HOFFMAN 2007			