



WALL LEGEND SEE STRUCTURAL SHEET #S1 # #S2 FOR FURTHER INFORMATION

<p>UL1305 1 hr. FIRE-RATED WALL: (1) LAYER OF 5/8" TYPE "X" FIRE-RATED GYP. BD. AT EACH SIDE OF 2x4 WOOD STUDS @ 16" O.C. EXTENDED TO THE UNDERSIDE OF WOOD ROOF / FLOOR TRUSSES.</p>	<p>INTERIOR WALLS: 5/8" GYP. BD. AT EACH SIDE OF 2x6 WOOD STUDS AT 16" O.C.</p>
<p>INTERIOR WALLS: 5/8" GYP. BD. AT EACH SIDE OF 2x4 WOOD STUDS AT 16" O.C.</p>	<p>EXTERIOR WALLS: 5/8" GYP. BOARD ON 2x6 WOOD STUDS AT 16" O.C. ON 1/2" EXT. GRADE FLYWOOD WITH VAPOR BARRIER AND VENEER SYSTEM. SEE ELEVATION FOR MORE INFO.</p>
<p>EXTERIOR WALLS: 5/8" GYP. BOARD ON 2x4 WOOD STUDS AT 16" O.C. ON 1/2" EXT. GRADE FLYWOOD WITH VAPOR BARRIER AND VENEER SYSTEM. SEE ELEVATION FOR MORE INFO.</p>	



DESCRIPTIONAL / DIMENSIONAL SECOND FLOOR PLAN
SCALE: 3/16" = 1'-0"

FIRST FLOOR SQUARE FOOTAGE	3,913
SECOND FLOOR SQUARE FOOTAGE	1,966
TOTAL SQUARE FOOTAGE	5,879

COMMERCIAL