



ELECTRICAL SYMBOL LEGEND	
SYMBOL	DESCRIPTION
S	STANDARD SWITCHES, 20 AMPERE, 120.277 VOLT, SINGLE POLE, MTD. AT 48" AFF UON ("D"=DIMMER, "3"=3-WAY, "4"=4-WAY, "H"=HINGED SWITCH)
	DUPLEX RECEPTACLE 20 AMPERE, 125 VOLT, MOUNTED AT 15" AFF UON
	DOUBLE DUPLEX RECEPTACLE 20 AMPERE, 125 VOLT, MOUNTED AT 15" AFF UON
J	JUNCTION BOX- MOUNTING HT AND SIZE AS REQUIRED BY CODE OR AS NOTED ON DWGS
	TELEPHONE/ CABLE JACK, MOUNTED AT 15" AFF UON
ETR	INDICATES EXISTING ELECTRICAL DEVICE- TO REMAIN
—SF	IN-WALL SPEAKER
⊙	IN-CEILING SPEAKER
C	MOUNTED AT COUNTER HEIGHT; APPROX. 42" AFF
GFI	GROUND FAULT INTERRUPTER
○	RECESSED CEILING LIGHT

NOTES:

1. (E) RECEPTACLES, LIGHTING, AND SWITCHES HAVE BEEN INDICATED FOR REFERENCE ONLY AND SHOULD BE V.I.F

2. ALL ELECTRICAL IS TO BE UPGRADED AND ADDITIONAL RECEPTACLES MUST BE ADDED AS NEEDED TO MEET ELECTRICAL CODE REQUIREMENTS. ONLY CLIENT SPECIFIED/DESIGN SPECIFIC RECEPTACLES HAVE BEEN INDICATED.

3. ELECTRICAL PANELS TO BE COMBINED AND RELOCATED AS INDICATED.

- = EXISTING WALL
- = EXISTING WALL TO BE REMOVED
- = NOT IN SCOPE OF WORK
- = MILLWORK TO BE REMOVED

1 SIXTH FLOOR ELECTRICAL PLAN
SCALE: 3/16"= 1'-0"