

MAYTAG®

Maytag® Top-Load

Washers

X/X/14



Maytag® Top-Load Washer MT 1

Sales Demonstration Modes

33812, 33842, 33872, 33891/2

Control Panel Demo

During this demo, the console will start a light dance and the controls will be locked.

- 1 Press POWER to turn washer on.
- 2 Turn the cycle knob to Clean Washer with affresh®.
- 3 Press WASH TEMP, SPIN SPEED, WASH TEMP, SPIN SPEED.
- 4 The Control Panel Demo will begin.
- 5 Power the washer off or press CANCEL to exit the demo.

Spin Demo:

During this demo, the washer will proceed through a series of spins.

- 1 Press POWER to turn the washer on.
- 2 Turn the cycle knob to Clean Washer with affresh®.
- 3 Press WASH TEMP, EXTRA RINSE, WASH TEMP, EXTRA RINSE.
- 4 The Spin Demo will begin.
- 5 Power the washer off or press CANCEL to exit the demo.



Key Features

- 3.6 Cu. Ft. Capacity
- Agitator Washer
- Handwash Cycle
- White Porcelain-On-Steel Drum

White 23302 (MVWC200BW)

X/X/14

Product Overview

Capacity	Motor Speeds	Max. Spin Speed	Controls	Wash Basket
3.6 Cu. Ft.	2	700 RPM	Rotary Electronic	White Porcelain-on-Steel

Wash System

Cycles	Wash System	Speed Switch	Water Levels	Water Temps
9	Agitator	No	4	4 — ATC

Motor

Drive System

Belt

Design

Size (H x W x D)

43" x 27-1/2" x 27"

Weight

121 lbs.

Matching Dryers

7/63312

Step-Up Dryers

7/63452 - IntelliDry® Sensor

Water Savings¹

35%

Energy Savings¹

28%

¹) Compared to pre-2004 traditional top load washers, average use, normal cycle.



23302

Maytag® Centennial®

Cycles(9)	Options(4)	Key Features
<input checked="" type="checkbox"/> Normal (3) <input checked="" type="checkbox"/> Delicate (Handwash) <input checked="" type="checkbox"/> Clean Washer w/ affresh® <input checked="" type="checkbox"/> Wrinkle Control (2) <input checked="" type="checkbox"/> Rinse/Spin <input checked="" type="checkbox"/> Drain/Spin <input type="checkbox"/> Bulky <input type="checkbox"/> Power Wash® <input type="checkbox"/> Cold Wash <input type="checkbox"/> Soak <input type="checkbox"/> Deep Water Wash <input type="checkbox"/> Sanitize w/ Oxi <input type="checkbox"/> Heavy Duty <input type="checkbox"/> Rinse/Drain & Spin <input type="checkbox"/> Whites <input type="checkbox"/> Rapid Wash <input type="checkbox"/> Sheets <input type="checkbox"/> Colors/Towels <input type="checkbox"/> Allergen <input type="checkbox"/> Active Wear	<input checked="" type="checkbox"/> Wash Temp (4) <input checked="" type="checkbox"/> Start/Pause <input checked="" type="checkbox"/> Load Size (4) <input checked="" type="checkbox"/> Rinse (4) <input type="checkbox"/> Soil Level <input type="checkbox"/> Fabric Softener <input type="checkbox"/> Extra Rinse <input type="checkbox"/> Spin Speed <input type="checkbox"/> Cycle Signal <input type="checkbox"/> Water Save <input type="checkbox"/> Delay Start <input type="checkbox"/> Clean Boost w/Heater <input type="checkbox"/> Oxi Treat Stains	<input checked="" type="checkbox"/> Maytag® Commercial Technology <input checked="" type="checkbox"/> Cycle Status Lights <input checked="" type="checkbox"/> Wide-Opening Lid <input checked="" type="checkbox"/> Gravity Bleach Dispenser <input type="checkbox"/> Fabric Softener Dispenser <input type="checkbox"/> Detergent Dispenser <input type="checkbox"/> QuietSeries™ Sound Package <input type="checkbox"/> Water Save Spray Rinse <input type="checkbox"/> PowerSpray Technology <input type="checkbox"/> SmoothClose™ Lid <input type="checkbox"/> Durable Glass Window <input type="checkbox"/> Oxi Dispenser

Electrical Requirements

Voltage	Amperage	Cord Length
120 Volts, 60 Hz	15 - 20 Amp, 3 Prong Circuit	5 ft.

Parts

Washer Tray	Washer Inlet Hose
29" x 31" - 98312	48027 Stainless Steel 52535 Rubber

Warranty

1-Year Parts, Labor



Key Features

- 3.6 Cu. Ft. Capacity
- Agitator Washer
- Power Wash® Cycle
- Cold Wash Cycle

White 23312 (MVWC300BW)

X/X/14

Product Overview

Capacity	Motor Speeds	Max. Spin Speed	Controls	Wash Basket
3.6 Cu. Ft.	2	700 RPM	Rotary Electronic	White Porcelain-on-Steel

Wash System

Cycles	Wash System	Speed Switch	Water Levels	Water Temps
10	Agitator	No	4	4 — ATC

Motor

Drive System

Belt

Design

Size (H x W x D)

43" x 27-1/2" x 27"

Weight

121 lbs.

Matching Dryers

7/63312

Step-Up Dryers

7/63452 - IntelliDry® Sensor

Water Savings¹

35%

Energy Savings¹

28%

Red Indicates step-up feature

¹) Compared to pre-2004 traditional top load washers, average use, normal cycle.



23312

Maytag® Centennial®

Cycles (10)	Options (5)	Key Features
<input checked="" type="checkbox"/> Normal <input checked="" type="checkbox"/> Delicate (Handwash) <input checked="" type="checkbox"/> Clean Washer w/ affresh® <input checked="" type="checkbox"/> Wrinkle Control <input checked="" type="checkbox"/> Rinse/Spin <input checked="" type="checkbox"/> Drain/Spin <input checked="" type="checkbox"/> Bulky (Bulky/Sheets) <input checked="" type="checkbox"/> Power Wash® <input checked="" type="checkbox"/> Cold Wash <input checked="" type="checkbox"/> Soak <input type="checkbox"/> Deep Water Wash <input type="checkbox"/> Sanitize w/ Oxi <input type="checkbox"/> Heavy Duty <input type="checkbox"/> Rinse/Drain & Spin <input type="checkbox"/> Whites <input type="checkbox"/> Rapid Wash <input type="checkbox"/> Sheets <input type="checkbox"/> Colors/Towels <input type="checkbox"/> Allergen <input type="checkbox"/> Active Wear	<input checked="" type="checkbox"/> Wash Temp (4) <input checked="" type="checkbox"/> Start/Pause <input checked="" type="checkbox"/> Load Size (4) <input checked="" type="checkbox"/> Rinse (4) <input checked="" type="checkbox"/> Soil Level (3) <input type="checkbox"/> Fabric Softener <input type="checkbox"/> Extra Rinse <input type="checkbox"/> Spin Speed <input type="checkbox"/> Cycle Signal <input type="checkbox"/> Water Save <input type="checkbox"/> Delay Start <input type="checkbox"/> Clean Boost w/Heater <input type="checkbox"/> Oxi Treat Stains	<input checked="" type="checkbox"/> Maytag® Commercial Technology <input checked="" type="checkbox"/> Cycle Status Lights <input checked="" type="checkbox"/> Wide-Opening Lid <input checked="" type="checkbox"/> Gravity Bleach Dispenser <input checked="" type="checkbox"/> Fabric Softener Dispenser <input type="checkbox"/> Detergent Dispenser <input type="checkbox"/> QuietSeries™ Sound Package <input type="checkbox"/> Water Save Spray Rinse <input type="checkbox"/> PowerSpray Technology <input type="checkbox"/> SmoothClose™ Lid <input type="checkbox"/> Durable Glass Window <input type="checkbox"/> Oxi Dispenser

Electrical Requirements

Voltage	Amperage	Cord Length
120 Volts, 60 Hz	15 - 20 Amp, 3 Prong Circuit	5 ft.

Parts

Washer Tray	Washer Inlet Hose
29" x 31" - 98312	48027 Stainless Steel 52535 Rubber

Warranty

1-Year Parts, Labor



Key Features

- 3.8 Cu. Ft. Capacity
- Power Wash® Cycle
- Deep Water Wash Cycle
- Fountain™ Impeller
- Stainless Steel Wash Basket

White 33452 (MVWC425BW)

X/X/14

Product Overview

Capacity	Motor Speeds	Max. Spin Speed	Controls	Wash Basket
3.8 Cu. Ft.	2	800 RPM	Rotary Electronic	Stainless Steel

Wash System

Cycles	Wash System	Speed Switch	Water Levels	Water Temps
11	Fountain™ Impeller	No	IntelliFill™ Automatic Water Levels	5 — ATC

Motor

Drive System

Belt

Design

Size (H x W x D)

43" x 27-1/2" x 27"

Weight

115 lbs.

Matching Dryers

7/63452

Step-Up Dryers

7/63462 - Sanitize Cycle

Water Savings¹

74%

Energy Savings¹

81%

Red Indicates step-up feature

¹) Compared to pre-2004 traditional top load washers, average use, normal cycle.



33452

Maytag® Centennial®

Cycles(11)	Options(5)	Key Features
<input checked="" type="checkbox"/> Normal <input checked="" type="checkbox"/> Delicate (Handwash) <input checked="" type="checkbox"/> Clean Washer w/ affresh® <input checked="" type="checkbox"/> Wrinkle Control <input checked="" type="checkbox"/> Rinse/Spin <input checked="" type="checkbox"/> Drain/Spin <input checked="" type="checkbox"/> Bulky (Bulky/Sheets) <input checked="" type="checkbox"/> Power Wash® <input checked="" type="checkbox"/> Cold Wash <input checked="" type="checkbox"/> Soak <input checked="" type="checkbox"/> Deep Water Wash <input type="checkbox"/> Sanitize w/ Oxi <input type="checkbox"/> Heavy Duty <input type="checkbox"/> Rinse/Drain & Spin <input type="checkbox"/> Whites <input type="checkbox"/> Rapid Wash <input type="checkbox"/> Sheets <input type="checkbox"/> Colors/Towels <input type="checkbox"/> Allergen <input type="checkbox"/> Active Wear	<input checked="" type="checkbox"/> Wash Temp (5) <input checked="" type="checkbox"/> Start/Pause <input type="checkbox"/> Load Size <input type="checkbox"/> Rinse <input checked="" type="checkbox"/> Soil Level (3) <input checked="" type="checkbox"/> Fabric Softener (On/Off) <input checked="" type="checkbox"/> Extra Rinse (On/Off) <input type="checkbox"/> Spin Speed <input type="checkbox"/> Cycle Signal <input type="checkbox"/> Water Save <input type="checkbox"/> Delay Start <input type="checkbox"/> Clean Boost w/Heater <input type="checkbox"/> Oxi Treat Stains	<input checked="" type="checkbox"/> Maytag® Commercial Technology <input checked="" type="checkbox"/> Cycle Status Lights <input checked="" type="checkbox"/> Wide-Opening Lid <input checked="" type="checkbox"/> Gravity Bleach Dispenser <input type="checkbox"/> Fabric Softener Dispenser <input type="checkbox"/> Detergent Dispenser <input type="checkbox"/> QuietSeries™ Sound Package <input type="checkbox"/> Water Save Spray Rinse <input type="checkbox"/> PowerSpray Technology <input type="checkbox"/> SmoothClose™ Lid <input type="checkbox"/> Durable Glass Window <input type="checkbox"/> Oxi Dispenser

Electrical Requirements

Voltage	Amperage	Cord Length
120 Volts, 60 Hz	15 - 20 Amp, 3 Prong Circuit	5 ft.

Parts

Washer Tray	Washer Inlet Hose
29" x 31" - 98312	48027 Stainless Steel 52535 Rubber

Warranty

1-Year Parts, Labor



Key Features

- 3.8 Cu. Ft. Capacity
- **PowerWash® System**
- Deep Water Wash Cycle
- Fountain™ Impeller
- Stainless Steel Wash Basket
- **QuietSeries™ Sound Package**
- 10-Year Limited Parts Warranty on Motor and Basket



White 33462 (MVWX500BW)

X/X/14

Product Overview

Capacity	Motor Speeds	Max. Spin Speed	Controls	Wash Basket
3.8 Cu. Ft.	3	800 RPM	Rotary Electronic	Stainless Steel

Wash System

Cycles	Wash System	Speed Switch	Water Levels	Water Temps
11	PowerWash® System	No	IntelliFill™ Automatic Water Levels	5 — ATC

Motor

Drive System

Belt

Design

Size (H x W x D)

43" x 27-1/2" x 27"

Weight

121 lbs.

Matching Dryers

7/63462

Step-Up Dryers

7/63812 - Advanced Moisture Sensing

Water Savings¹

74%

Energy Savings¹

81%

Red Indicates step-up feature

¹) Compared to pre-2004 traditional top load washers, average use, normal cycle.



Washers

Maytag® Top-Load Washer MT 9

33462

Maytag® Bravos X®

Cycles(11)	Options(5)	Key Features
<input checked="" type="checkbox"/> Normal <input checked="" type="checkbox"/> Delicate (Handwash) <input checked="" type="checkbox"/> Clean Washer w/ affresh® <input checked="" type="checkbox"/> Wrinkle Control <input checked="" type="checkbox"/> Rinse/Spin <input checked="" type="checkbox"/> Drain/Spin <input checked="" type="checkbox"/> Bulky (Bulky/Sheets) <input checked="" type="checkbox"/> Power Wash® <input checked="" type="checkbox"/> Cold Wash <input checked="" type="checkbox"/> Soak <input checked="" type="checkbox"/> Deep Water Wash <input type="checkbox"/> Sanitize w/ Oxi <input type="checkbox"/> Heavy Duty <input type="checkbox"/> Rinse/Drain & Spin <input type="checkbox"/> Whites <input type="checkbox"/> Rapid Wash <input type="checkbox"/> Sheets <input type="checkbox"/> Colors/Towels <input type="checkbox"/> Allergen <input type="checkbox"/> Active Wear	<input checked="" type="checkbox"/> Wash Temp (5) <input checked="" type="checkbox"/> Start/Pause <input type="checkbox"/> Load Size <input type="checkbox"/> Rinse <input checked="" type="checkbox"/> Soil Level (4) <input checked="" type="checkbox"/> Fabric Softener (On/Off) <input checked="" type="checkbox"/> Extra Rinse (On/Off) <input type="checkbox"/> Spin Speed <input type="checkbox"/> Cycle Signal <input type="checkbox"/> Water Save <input type="checkbox"/> Delay Start <input type="checkbox"/> Clean Boost w/Heater <input type="checkbox"/> Oxi Treat Stains	<input checked="" type="checkbox"/> Maytag® Commercial Technology <input checked="" type="checkbox"/> Cycle Status Lights <input checked="" type="checkbox"/> Wide-Opening Lid <input type="checkbox"/> Gravity Bleach Dispenser <input checked="" type="checkbox"/> Fabric Softener Dispenser <input checked="" type="checkbox"/> Detergent Dispenser <input checked="" type="checkbox"/> QuietSeries™ Sound Package <input type="checkbox"/> Water Save Spray Rinse <input type="checkbox"/> PowerSpray Technology <input type="checkbox"/> SmoothClose™ Lid <input type="checkbox"/> Durable Glass Window <input type="checkbox"/> Oxi Dispenser

Electrical Requirements

Voltage	Amperage	Cord Length
120 Volts, 60 Hz	15 - 20 Amp, 3 Prong Circuit	5 ft.

Parts

Washer Tray	Washer Inlet Hose
29" x 31" - 98312	48027 Stainless Steel 52535 Rubber

Warranty

10-Year Limited Parts Warranty on Washer Motor and Stainless Steel Wash Basket



Key Features

- 4.5 Cu. Ft. Capacity
- PowerWash® System
- PowerSpray Technology
- IntelliClean™ Impeller
- Stainless Steel Wash Basket
- QuietSeries™ Sound Package
- Water Save Spray Rinse



White 33812 (MVWB700BW)

X/X/14

Product Overview

Capacity	Motor Speeds	Max. Spin Speed	Controls	Wash Basket
4.5 Cu. Ft.	3	1,100 RPM w/ Max Extract	Electronic w/ LED Display	Stainless Steel

Wash System

Cycles	Wash System	Speed Switch	Water Levels	Water Temps
10	PowerWash® System	Yes	IntelliFill™ Automatic Water Levels	4 — ATC

Motor

Drive System

Direct

Design

Size (H x W x D)

42" x 27-9/16" x 27-5/8"

Weight

150 lbs.

Matching Dryers

7/63812

Step-Up Dryers

7/63842 - Auto Refresh
w/ Steam Cycle

Water Savings¹

74%

Energy Savings¹

82%

Red Indicates step-up feature

¹ Compared to pre-2004 traditional top load washers, average use, normal cycle.



Washers

Maytag® Top-Load Washer MT 11

33812

Maytag® Bravos XL®

Cycles (10)	Options (8)	Key Features
<input checked="" type="checkbox"/> Normal <input checked="" type="checkbox"/> Delicate (Handwash) <input checked="" type="checkbox"/> Clean Washer w/ affresh® <input type="checkbox"/> Wrinkle Control <input type="checkbox"/> Rinse/Spin <input type="checkbox"/> Drain/Spin <input checked="" type="checkbox"/> Bulky <input checked="" type="checkbox"/> Power Wash® <input type="checkbox"/> Cold Wash <input type="checkbox"/> Soak <input type="checkbox"/> Deep Water Wash <input type="checkbox"/> Sanitize w/ Oxi <input checked="" type="checkbox"/> Heavy Duty <input checked="" type="checkbox"/> Rinse/Drain & Spin <input checked="" type="checkbox"/> Whites <input checked="" type="checkbox"/> Rapid Wash <input checked="" type="checkbox"/> Sheets <input type="checkbox"/> Colors/Towels <input type="checkbox"/> Allergen <input type="checkbox"/> Active Wear	<input checked="" type="checkbox"/> Wash Temp (4) <input checked="" type="checkbox"/> Start/Pause <input type="checkbox"/> Load Size <input type="checkbox"/> Rinse <input checked="" type="checkbox"/> Soil Level (3) <input checked="" type="checkbox"/> Fabric Softener <input checked="" type="checkbox"/> Extra Rinse <input checked="" type="checkbox"/> Spin Speed (3) <input checked="" type="checkbox"/> Cycle Signal (Hi/Low/Off) <input checked="" type="checkbox"/> Water Save <input type="checkbox"/> Delay Start <input type="checkbox"/> Clean Boost w/Heater <input type="checkbox"/> Oxi Treat Stains	<input checked="" type="checkbox"/> Maytag® Commercial Technology <input checked="" type="checkbox"/> Cycle Status Lights <input checked="" type="checkbox"/> Wide-Opening Lid <input checked="" type="checkbox"/> Gravity Bleach Dispenser <input checked="" type="checkbox"/> Fabric Softener Dispenser <input checked="" type="checkbox"/> Detergent Dispenser <input checked="" type="checkbox"/> QuietSeries™ Sound Package <input checked="" type="checkbox"/> Water Save Spray Rinse <input checked="" type="checkbox"/> PowerSpray Technology <input checked="" type="checkbox"/> SmoothClose™ Lid <input type="checkbox"/> Durable Glass Window <input type="checkbox"/> Oxi Dispenser

Electrical Requirements

Voltage	Amperage	Cord Length
120 Volts, 60 Hz	15 - 20 Amp, 3 Prong Circuit	5 ft.

Parts

Washer Tray	Washer Inlet Hose
29" x 31" - 98312	48027 Stainless Steel 52535 Rubber

Warranty

10-Year Limited Parts Warranty on Washer Motor and Stainless Steel Wash Basket



Key Features

- 4.5 Cu. Ft. Capacity
- PowerWash® System
- PowerSpray Technology
- IntelliClean™ Impeller
- Stainless Steel Wash Basket
- Water Save Spray Rinse
- **Durable Glass Window**



White 33842 (MVWB725BW)

X/X/14

Product Overview

Capacity	Motor Speeds	Max. Spin Speed	Controls	Wash Basket
4.5 Cu. Ft.	3	1,100 RPM w/ Max Extract	Electronic w/ LED Display	Stainless Steel

Wash System

Cycles	Wash System	Speed Switch	Water Levels	Water Temps
10	PowerWash® System	Yes	IntelliFill™ Automatic Water Levels	4 — ATC

Motor

Drive System
Direct

Design

Size (H x W x D)	Weight
42" x 27-9/16" x 27-5/8"	150 lbs.

Matching Dryers

7/63842

Step-Up Dryers

7/63872 - Sanitize Cycle

Water Savings¹

74%

Energy Savings¹

82%

Red Indicates step-up feature

¹) Compared to pre-2004 traditional top load washers, average use, normal cycle.



Washers

Maytag® Top-Load Washer MT 13

33842

Maytag® Bravos XL®

Cycles (10)	Options (8)	Key Features
<input checked="" type="checkbox"/> Normal <input checked="" type="checkbox"/> Delicate (Handwash) <input checked="" type="checkbox"/> Clean Washer w/ affresh® <input type="checkbox"/> Wrinkle Control <input type="checkbox"/> Rinse/Spin <input type="checkbox"/> Drain/Spin <input checked="" type="checkbox"/> Bulky <input checked="" type="checkbox"/> Power Wash® <input type="checkbox"/> Cold Wash <input type="checkbox"/> Soak <input type="checkbox"/> Deep Water Wash <input type="checkbox"/> Sanitize w/ Oxi <input checked="" type="checkbox"/> Heavy Duty <input checked="" type="checkbox"/> Rinse/Drain & Spin <input checked="" type="checkbox"/> Whites <input checked="" type="checkbox"/> Rapid Wash <input checked="" type="checkbox"/> Sheets <input type="checkbox"/> Colors/Towels <input type="checkbox"/> Allergen <input type="checkbox"/> Active Wear	<input checked="" type="checkbox"/> Wash Temp (4) <input checked="" type="checkbox"/> Start/Pause <input type="checkbox"/> Load Size <input type="checkbox"/> Rinse <input checked="" type="checkbox"/> Soil Level (3) <input checked="" type="checkbox"/> Fabric Softener <input checked="" type="checkbox"/> Extra Rinse <input checked="" type="checkbox"/> Spin Speed (3) <input checked="" type="checkbox"/> Cycle Signal (Hi/Low/Off) <input checked="" type="checkbox"/> Water Save <input type="checkbox"/> Delay Start <input type="checkbox"/> Clean Boost w/Heater <input type="checkbox"/> Oxi Treat Stains	<input checked="" type="checkbox"/> Maytag® Commercial Technology <input checked="" type="checkbox"/> Cycle Status Lights <input checked="" type="checkbox"/> Wide-Opening Lid <input checked="" type="checkbox"/> Gravity Bleach Dispenser <input checked="" type="checkbox"/> Fabric Softener Dispenser <input checked="" type="checkbox"/> Detergent Dispenser <input checked="" type="checkbox"/> QuietSeries™ Sound Package <input checked="" type="checkbox"/> Water Save Spray Rinse <input checked="" type="checkbox"/> PowerSpray Technology <input checked="" type="checkbox"/> SmoothClose™ Lid <input checked="" type="checkbox"/> Durable Glass Window <input type="checkbox"/> Oxi Dispenser

Electrical Requirements

Voltage	Amperage	Cord Length
120 Volts, 60 Hz	15 - 20 Amp, 3 Prong Circuit	5 ft.

Parts

Washer Tray	Washer Inlet Hose
29" x 31" - 98312	48027 Stainless Steel 52535 Rubber

Warranty

10-Year Limited Parts Warranty on Washer Motor and Stainless Steel Wash Basket



Key Features

- 4.8 Cu. Ft. Capacity
- PowerWash® System
- PowerSpray Technology
- IntelliClean™ Impeller
- Water Save Spray Rinse
- Allergen Cycle
- Cold Wash Cycle
- Durable, Smoked Glass Window



White 33872 (MVWB880BW)

X/X/14

Product Overview

Capacity	Motor Speeds	Max. Spin Speed	Controls	Wash Basket
4.8 Cu. Ft.	3	1,100 RPM w/ Max Extract	Electronic w/ LED Display	Stainless Steel

Wash System

Cycles	Wash System	Speed Switch	Water Levels	Water Temps
13	PowerWash® System	Yes	IntelliFill™ Automatic Water Levels	4 — ATC

Motor

Drive System

Direct

Design

Size (H x W x D)

45-1/8" x 27-9/16" x 27-5/8"

Weight

160 lbs.

Matching Dryers

7/63872

Step-Up Dryers

7/63892 - Custom Refresh w/ Steam Cycle

Water Savings¹

74%

Energy Savings¹

82%

Red Indicates step-up feature

¹) Compared to pre-2004 traditional top load washers, average use, normal cycle.



Washers

Maytag® Top-Load Washer MT 15

33872

Maytag® Bravos XL®

Cycles(13)	Options(8)	Key Features
<input checked="" type="checkbox"/> Normal <input checked="" type="checkbox"/> Delicate (Handwash) <input checked="" type="checkbox"/> Clean Washer w/ affresh® <input type="checkbox"/> Wrinkle Control <input type="checkbox"/> Rinse/Spin <input type="checkbox"/> Drain/Spin <input checked="" type="checkbox"/> Bulky <input checked="" type="checkbox"/> Power Wash® <input checked="" type="checkbox"/> Cold Wash <input type="checkbox"/> Soak <input type="checkbox"/> Deep Water Wash <input type="checkbox"/> Sanitize w/ Oxi <input checked="" type="checkbox"/> Heavy Duty <input checked="" type="checkbox"/> Rinse/Drain & Spin <input checked="" type="checkbox"/> Whites <input checked="" type="checkbox"/> Rapid Wash <input checked="" type="checkbox"/> Sheets <input checked="" type="checkbox"/> Colors/Towels <input checked="" type="checkbox"/> Allergen <input type="checkbox"/> Active Wear	<input checked="" type="checkbox"/> Wash Temp (4) <input checked="" type="checkbox"/> Start/Pause <input type="checkbox"/> Load Size <input type="checkbox"/> Rinse <input checked="" type="checkbox"/> Soil Level (4) <input checked="" type="checkbox"/> Fabric Softener <input checked="" type="checkbox"/> Extra Rinse <input checked="" type="checkbox"/> Spin Speed (4) <input checked="" type="checkbox"/> Cycle Signal (Hi/Low/Off) <input checked="" type="checkbox"/> Water Save <input type="checkbox"/> Delay Start <input type="checkbox"/> Clean Boost w/Heater <input type="checkbox"/> Oxi Treat Stains	<input checked="" type="checkbox"/> Maytag® Commercial Technology <input checked="" type="checkbox"/> Cycle Status Lights <input checked="" type="checkbox"/> Wide-Opening Lid <input checked="" type="checkbox"/> Gravity Bleach Dispenser <input checked="" type="checkbox"/> Fabric Softener Dispenser <input checked="" type="checkbox"/> Detergent Dispenser <input checked="" type="checkbox"/> QuietSeries™ Sound Package <input checked="" type="checkbox"/> Water Save Spray Rinse <input checked="" type="checkbox"/> PowerSpray Technology <input checked="" type="checkbox"/> SmoothClose™ Lid <input checked="" type="checkbox"/> Durable, Smoked Glass Window <input type="checkbox"/> Oxi Dispenser

Electrical Requirements

Voltage	Amperage	Cord Length
120 Volts, 60 Hz	15 - 20 Amp, 3 Prong Circuit	5 ft.

Parts

Washer Tray	Washer Inlet Hose
29" x 31" - 98312	48027 Stainless Steel 52535 Rubber

Warranty

10-Year Limited Parts Warranty on Washer Motor and Stainless Steel Wash Basket



Key Features

- 4.8 Cu. Ft. Capacity
- **Steam Washer**
- **Sanitary Wash Cycle w/ Oxi & Steam**
- **Clean Boost w/ Heater**
- Allergen Cycle
- IntelliClean™ Impeller
- PowerSpray Technology
- PowerWash® Cycle
- Water Save Spray Rinse



- Chrome Shadow 33891 (MVWB980BG)
- White 33892 (MVWB980BW)

X/X/14

Product Overview

Capacity	Motor Speeds	Max. Spin Speed	Controls	Wash Basket
4.8 Cu. Ft.	4	1,100 RPM w/ Max Extract	Electronic w/ LED Display	Stainless Steel

Wash System

Cycles	Wash System	Speed Switch	Water Levels	Water Temps
16	PowerWash® System	Yes	IntelliFill™ Automatic Water Levels	5 — ATC

Motor

Drive System
Direct

Design

Size (H x W x D)	Weight
45-1/8" x 27-9/16" x 27-5/8"	160 lbs.

Matching Dryers

7/63891/2

Step-Up Dryers

Not Applicable

Water Savings¹

74%

Energy Savings¹

82%

Red Indicates step-up feature

¹) Compared to pre-2004 traditional top load washers, average use, normal cycle.



Washers

Maytag® Top-Load Washer MT 17

33891/2

Maytag® Bravos XL®

Cycles (16)	Options (11)	Key Features
<input checked="" type="checkbox"/> Normal <input checked="" type="checkbox"/> Delicate (Handwash) <input checked="" type="checkbox"/> Clean Washer w/ affresh® <input type="checkbox"/> Wrinkle Control <input type="checkbox"/> Rinse/Spin <input type="checkbox"/> Drain/Spin <input checked="" type="checkbox"/> Bulky <input checked="" type="checkbox"/> Power Wash® <input checked="" type="checkbox"/> Cold Wash <input checked="" type="checkbox"/> Soak <input type="checkbox"/> Deep Water Wash <input checked="" type="checkbox"/> Sanitary w/ Oxi & Steam <input checked="" type="checkbox"/> Heavy Duty <input checked="" type="checkbox"/> Rinse/Drain & Spin <input checked="" type="checkbox"/> Whites <input checked="" type="checkbox"/> Rapid Wash <input checked="" type="checkbox"/> Sheets <input checked="" type="checkbox"/> Colors/Towels <input checked="" type="checkbox"/> Allergen <input checked="" type="checkbox"/> Active Wear	<input checked="" type="checkbox"/> Wash Temp (5) <input checked="" type="checkbox"/> Start/Pause <input type="checkbox"/> Load Size <input type="checkbox"/> Rinse <input checked="" type="checkbox"/> Soil Level (4) <input checked="" type="checkbox"/> Fabric Softener <input checked="" type="checkbox"/> Extra Rinse <input checked="" type="checkbox"/> Spin Speed (4) <input checked="" type="checkbox"/> Cycle Signal (Hi/Low/Off) <input checked="" type="checkbox"/> Water Save <input checked="" type="checkbox"/> Delay Start (up to 18 Hrs.) <input checked="" type="checkbox"/> Clean Boost w/Heater <input checked="" type="checkbox"/> Oxi Treat Stains	<input checked="" type="checkbox"/> Maytag® Commercial Technology <input checked="" type="checkbox"/> Cycle Status Lights <input checked="" type="checkbox"/> Wide-Opening Lid <input checked="" type="checkbox"/> Gravity Bleach Dispenser <input checked="" type="checkbox"/> Fabric Softener Dispenser <input checked="" type="checkbox"/> Detergent Dispenser <input checked="" type="checkbox"/> QuietSeries™ Sound Package <input checked="" type="checkbox"/> Water Save Spray Rinse <input checked="" type="checkbox"/> PowerSpray Technology <input checked="" type="checkbox"/> SmoothClose™ Lid <input checked="" type="checkbox"/> Durable, Smoked Glass Window <input checked="" type="checkbox"/> Oxi Dispenser

Electrical Requirements

Voltage	Amperage	Cord Length
120 Volts, 60 Hz	15 - 20 Amp, 3 Prong Circuit	5 ft.

Parts

Washer Tray	Washer Inlet Hose
29" x 31" - 98312	48027 Stainless Steel 52535 Rubber

Warranty

10-Year Limited Parts Warranty on Washer Motor and Stainless Steel Wash Basket

Maytag® Advantages

- This washer delivers the Best Cleaning in its Class, enabled by the PowerWash® cycle.

MAYTAG®

Maytag® Matching

Dryers

XIX/14



Sales Demonstration Modes



Key Features

- 7.0 Cu. Ft. Capacity
- GentleBreeze™ Drying System w/ Wrinkle Control
- Interior Drum Light
- DuraCushion™ Dryer Drum

White 7/63312 (MGD/MEDC300BW)

X/X/14

Product Overview

Capacity	Filter	Controls	Drum Material	Dryer Rack
7.0 Cu. Ft.	Top	Electro-Mechanical	Powder Coat	See Parts Section for Details

Dry System

Cycles	Dry Control	Temps.	Temp. Settings
14	GentleBreeze™ Drying System	3	High, Medium, Low

Design

Size (H x W)	Depth	Weight
43" x 29"	Gas: 29-1/4" Electric: 29-1/4"	Gas: 113 lbs. Electric: 109 lbs.

Matching Washers

23312

Step-Up Washers

33452 - Stainless Steel Wash Basket and Fountain™ Impeller

7/63312

Maytag® Centennial®

Cycles(14)	Options(2)	Key Features
<input checked="" type="checkbox"/> Timed Dry (7) <input checked="" type="checkbox"/> Air Fluff/No Heat (3) <input checked="" type="checkbox"/> Auto Dry w/ Wrinkle Control (4) <input checked="" type="checkbox"/> Wrinkle Control <input type="checkbox"/> Sensor Dry <input type="checkbox"/> Normal <input type="checkbox"/> Delicate <input type="checkbox"/> Heavy Duty <input type="checkbox"/> Bulky <input type="checkbox"/> Small Loads <input type="checkbox"/> Sheets <input type="checkbox"/> Freshen Up <input type="checkbox"/> Auto Refresh w/ Steam <input type="checkbox"/> Towels <input type="checkbox"/> Sanitize <input type="checkbox"/> Active Wear <input type="checkbox"/> Denim <input type="checkbox"/> Custom Refresh w/ Steam	<input checked="" type="checkbox"/> Temp Level (3) <input checked="" type="checkbox"/> End of Cycle Signal (On/Off) <input type="checkbox"/> Wrinkle Control <input type="checkbox"/> Dryness Level <input type="checkbox"/> Damp Dry Signal <input type="checkbox"/> Time Adjust <input type="checkbox"/> Start/Pause <input type="checkbox"/> Drum Light <input type="checkbox"/> Wrinkle Prevent w/ Steam <input type="checkbox"/> Wrinkle Prevent without Steam <input type="checkbox"/> Reduce Static <input type="checkbox"/> Steam Boost <input type="checkbox"/> Custom Refresh	<input checked="" type="checkbox"/> Reversible, Side-Swing Door <input checked="" type="checkbox"/> Maytag® Commercial Technology <input checked="" type="checkbox"/> Interior Drum Light <input type="checkbox"/> IntelliDry® Sensor <input type="checkbox"/> Auto Moisture Sensing <input type="checkbox"/> QuietSeries™ Sound Package <input type="checkbox"/> Advanced Moisture Sensing <input type="checkbox"/> Check Lint Screen Indicator <input type="checkbox"/> LCD Screen w/ Time Remaining Display <input type="checkbox"/> Enhanced Airflow Monitor <input type="checkbox"/> Direct Y-Connector Water Hook-Up <input type="checkbox"/> Smoked Glass Window

Parts & Kits

Door Reversal	LP Conversion Kit	Cord
Reversible, No Additional Kit Required	49572A	Gas: 110v Cord Included

Venting

Rear

See Installation page IG 35 for details

Side/Bottom Venting ¹	Vent - Left	Vent - Right	Vent - Bottom
Gas	Not Applicable	Not Applicable	Not Applicable
Electric	Not Applicable	Not Applicable	Not Applicable

Order through Sears Parts and Services: 1-800-469-4663

Special Instructions

Warranty

1-Year Parts, Labor

1) Internal venting kit only.



Key Features

- 7.0 Cu. Ft. Capacity
- Delicate Cycle
- **Wrinkle Control Option (90 Min.)**
- GentleBreeze™ Drying System w/ IntelliDry® Sensor
- DuraCushion™ Dryer Drum

White 7/63452 (MGD/MEDC400BW)

X/X/14

Product Overview

Capacity	Filter	Controls	Drum Material	Dryer Rack
7.0 Cu. Ft.	Top	Electro-Mechanical	Powder Coat	See Parts Section for Details

Dry System

Cycles	Dry Control	Temps.	Temp. Settings
12	GentleBreeze™ Drying System w/ IntelliDry® Sensor	4	High, Medium, Low, Air Fluff

Design

Size (H x W)	Depth	Weight
43" x 29"	Gas: 29-1/4" Electric: 29-1/4"	Gas: 113 lbs. Electric: 109 lbs.

Matching Washers

33452

Step-Up Washers

33462 - PowerWash® System

Red Indicates step-up feature

7/63452

Maytag® Centennial®

Cycles(12)	Options(3)	Key Features
<input checked="" type="checkbox"/> Timed Dry (7) <input type="checkbox"/> Air Fluff/No Heat <input type="checkbox"/> Auto Dry <input checked="" type="checkbox"/> Wrinkle Control <input checked="" type="checkbox"/> Sensor Dry (4) <input type="checkbox"/> Normal <input type="checkbox"/> Delicate <input type="checkbox"/> Heavy Duty <input type="checkbox"/> Bulky <input type="checkbox"/> Small Loads <input type="checkbox"/> Sheets <input type="checkbox"/> Freshen Up <input type="checkbox"/> Auto Refresh w/ Steam <input type="checkbox"/> Towels <input type="checkbox"/> Sanitize <input type="checkbox"/> Active Wear <input type="checkbox"/> Denim <input type="checkbox"/> Custom Refresh w/ Steam	<input checked="" type="checkbox"/> Temp Level (4) <input checked="" type="checkbox"/> End of Cycle Signal (On/Off) <input checked="" type="checkbox"/> Wrinkle Control (90 Min., Off) <input type="checkbox"/> Dryness Level <input type="checkbox"/> Damp Dry Signal <input type="checkbox"/> Time Adjust <input type="checkbox"/> Start/Pause <input type="checkbox"/> Drum Light <input type="checkbox"/> Wrinkle Prevent w/ Steam <input type="checkbox"/> Wrinkle Prevent without Steam <input type="checkbox"/> Reduce Static <input type="checkbox"/> Steam Boost <input type="checkbox"/> Custom Refresh	<input checked="" type="checkbox"/> Reversible, Side-Swing Door <input checked="" type="checkbox"/> Maytag® Commercial Technology <input checked="" type="checkbox"/> Interior Drum Light <input checked="" type="checkbox"/> IntelliDry® Sensor <input checked="" type="checkbox"/> Auto Moisture Sensing <input type="checkbox"/> QuietSeries™ Sound Package <input type="checkbox"/> Advanced Moisture Sensing <input type="checkbox"/> Check Lint Screen Indicator <input type="checkbox"/> LCD Screen w/ Time Remaining Display <input type="checkbox"/> Enhanced Airflow Monitor <input type="checkbox"/> Direct Y-Connector Water Hook-Up <input type="checkbox"/> Smoked Glass Window

Parts & Kits

Door Reversal	LP Conversion Kit	Cord
Reversible, No Additional Kit Required	49572A	Gas: 110v Cord Included

Venting

Rear

See Installation page IG 35 for details

Side/Bottom Venting ¹	Vent - Left	Vent - Right	Vent - Bottom
Gas	Not Applicable	Not Applicable	Not Applicable
Electric	Not Applicable	Not Applicable	Not Applicable

Order through Sears Parts and Services: 1-800-469-4663

Special Instructions

Warranty

1-Year Parts, Labor

1) Internal venting kit only.



Key Features

- 7.0 Cu. Ft. Capacity
- **Sanitize**
- Wrinkle Control Option (up to 120 Min.)
- GentleBreeze™ Drying System w/ IntelliDry® Sensor
- DuraCushion™ Dryer Drum

White 7/63462 (MGD/MEDX500BW)

X/X/14

Product Overview

Capacity	Filter	Controls	Drum Material	Dryer Rack
7.0 Cu. Ft.	Top	Electro-Mechanical	Powder Coat	See Parts Section for Details

Dry System

Cycles	Dry Control	Temps.	Temp. Settings
11	GentleBreeze™ Drying System w/ IntelliDry® Sensor	5	Sanitize , High, Medium, Low, Air Fluff

Design

Size (H x W)	Depth	Weight
43" x 29"	Gas: 29-1/4" Electric: 29-1/4"	Gas: 113 lbs. Electric: 109 lbs.

Matching Washers

33462

Step-Up Washers

33812 - 4.5 Cu. Ft. Capacity

Red Indicates step-up feature



Dryers

Maytag® Matching Dryer MT 25

7/63462

Maytag® Bravos X®

Cycles(11)	Options(3)	Key Features
<input checked="" type="checkbox"/> Timed Dry (7) <input type="checkbox"/> Air Fluff/No Heat <input type="checkbox"/> Auto Dry <input checked="" type="checkbox"/> Wrinkle Control <input checked="" type="checkbox"/> Sensor Dry (3) <input type="checkbox"/> Normal <input type="checkbox"/> Delicate <input type="checkbox"/> Heavy Duty <input type="checkbox"/> Bulky <input type="checkbox"/> Small Loads <input type="checkbox"/> Sheets <input type="checkbox"/> Freshen Up <input type="checkbox"/> Auto Refresh w/ Steam <input type="checkbox"/> Towels <input type="checkbox"/> Sanitize <input type="checkbox"/> Active Wear <input type="checkbox"/> Denim <input type="checkbox"/> Custom Refresh w/ Steam	<input checked="" type="checkbox"/> Temp Level (5) <input checked="" type="checkbox"/> End of Cycle Signal (High/Low/Off) <input checked="" type="checkbox"/> Wrinkle Control (120 Min., 60 Min., Off) <input type="checkbox"/> Dryness Level <input type="checkbox"/> Damp Dry Signal <input type="checkbox"/> Time Adjust <input type="checkbox"/> Start/Pause <input type="checkbox"/> Drum Light <input type="checkbox"/> Wrinkle Prevent w/ Steam <input type="checkbox"/> Wrinkle Prevent without Steam <input type="checkbox"/> Reduce Static <input type="checkbox"/> Steam Boost <input type="checkbox"/> Custom Refresh	<input checked="" type="checkbox"/> Reversible, Side-Swing Door <input checked="" type="checkbox"/> Maytag® Commercial Technology <input checked="" type="checkbox"/> Interior Drum Light <input checked="" type="checkbox"/> IntelliDry® Sensor <input checked="" type="checkbox"/> Auto Moisture Sensing <input checked="" type="checkbox"/> QuietSeries™ Sound Package <input type="checkbox"/> Advanced Moisture Sensing <input type="checkbox"/> Check Lint Screen Indicator <input type="checkbox"/> LCD Screen w/ Time Remaining Display <input type="checkbox"/> Enhanced Airflow Monitor <input type="checkbox"/> Direct Y-Connector Water Hook-Up <input type="checkbox"/> Smoked Glass Window

Parts & Kits

Door Reversal	LP Conversion Kit	Cord
Reversible, No Additional Kit Required	—	Gas: 110v Cord Included

Venting

4-Way (rear, left, right, bottom)
 See Installation page IG 35 for details

Side/Bottom Venting ¹	Vent - Left	Vent - Right	Vent - Bottom
Gas	W10470674	W10470674	W10470674
Electric	W10470674	W10470674	W10470674

Order through Sears Parts and Services: 1-800-469-4663

Special Instructions

Warranty

1-Year Parts, Labor

¹) Internal venting kit only.



Key Features

- 7.3 Cu. Ft. Capacity
- Enhanced Air Flow Monitor
- LCD Screen w/ Time Remaining
- GentleBreeze™ Drying System w/ Advanced Moisture Sensing
- Damp Dry Signal
- DuraCushion™ Dryer Drum

White 7/63812 (MGD/MEDB700BW)

X/X/14

Product Overview

Capacity	Filter	Controls	Drum Material	Dryer Rack
7.3 Cu. Ft.	Upfront	Electronic	Painted Steel	See Parts Section for Details

Dry System

Cycles	Dry Control	Temps.	Temp. Settings
9	GentleBreeze™ Drying System w/ Advanced Moisture Sensing	5	High, Medium, Low, Extra Low, Air Only

Design

Size (H x W)	Depth	Weight
42" x 29"	Gas: 29-1/4" Electric: 29-1/4"	Gas: 155 lbs. Electric: 152 lbs.

Matching Washers

33812

Step-Up Washers

33842 - Durable Glass Window

Red Indicates step-up feature



Dryers

7/63812

Maytag® Bravos XL®

Cycles (9)	Options (8)	Key Features
<input checked="" type="checkbox"/> Timed Dry <input type="checkbox"/> Air Fluff/No Heat <input type="checkbox"/> Auto Dry <input checked="" type="checkbox"/> Wrinkle Control <input type="checkbox"/> Sensor Dry <input checked="" type="checkbox"/> Normal <input checked="" type="checkbox"/> Delicate <input checked="" type="checkbox"/> Heavy Duty <input checked="" type="checkbox"/> Bulky <input checked="" type="checkbox"/> Small Loads <input checked="" type="checkbox"/> Sheets <input checked="" type="checkbox"/> Freshen Up <input type="checkbox"/> Auto Refresh w/ Steam <input type="checkbox"/> Towels <input type="checkbox"/> Sanitize <input type="checkbox"/> Active Wear <input type="checkbox"/> Denim <input type="checkbox"/> Custom Refresh w/ Steam	<input checked="" type="checkbox"/> Temp Level (5) <input checked="" type="checkbox"/> End of Cycle Signal (Hi/Low/Off) <input checked="" type="checkbox"/> Wrinkle Control (Wrinkle Prevent, up to 120 Min.) <input checked="" type="checkbox"/> Dryness Level (4) <input checked="" type="checkbox"/> Damp Dry Signal <input checked="" type="checkbox"/> Time Adjust (More Time/Less Time) <input checked="" type="checkbox"/> Start/Pause <input checked="" type="checkbox"/> Drum Light <input type="checkbox"/> Wrinkle Prevent w/ Steam <input type="checkbox"/> Wrinkle Prevent without Steam <input type="checkbox"/> Reduce Static <input type="checkbox"/> Steam Boost <input type="checkbox"/> Custom Refresh	<input checked="" type="checkbox"/> Reversible, Side-Swing Door <input checked="" type="checkbox"/> Maytag® Commercial Technology <input checked="" type="checkbox"/> Interior Drum Light <input checked="" type="checkbox"/> IntelliDry® Sensor <input type="checkbox"/> Auto Moisture Sensing <input checked="" type="checkbox"/> QuietSeries™ Sound Package <input checked="" type="checkbox"/> Advanced Moisture Sensing <input checked="" type="checkbox"/> Check Lint Screen Indicator <input checked="" type="checkbox"/> LCD Screen w/ Time Remaining Display <input checked="" type="checkbox"/> Enhanced Airflow Monitor <input type="checkbox"/> Direct Y-Connector Water Hook-Up <input type="checkbox"/> Smoked Glass Window

Parts & Kits

Door Reversal	LP Conversion Kit	Cord
Reversible, No Additional Kit Required	—	Gas: 110v Cord Included

Venting

2-Way (rear, bottom)

See Installation page IG 35 for details

Side/Bottom Venting ¹	Vent - Left	Vent - Right	Vent - Bottom
Gas	Not Applicable	Not Applicable	49610
Electric	Not Applicable	Not Applicable	49610

Order through Sears Parts and Services: 1-800-469-4663

Special Instructions	Warranty
	1-Year Parts, Labor

1) Internal venting kit only.



Key Features

- 7.3 Cu. Ft. Capacity
- **Auto Refresh w/ Steam Cycle**
- Wrinkle Prevent Option
- LCD Screen w/ Time Remaining
- GentleBreeze™ Drying System w/ Advanced Moisture Sensing
- Damp Dry Signal
- DuraCushion™ Dryer Drum

White 7/63842 (MGD/MEDB725BW)

X/X/14

Product Overview

Capacity	Filter	Controls	Drum Material	Dryer Rack
7.3 Cu. Ft.	Upfront	Electronic	Painted Steel	See Parts Section for Details

Dry System

Cycles	Dry Control	Temps.	Temp. Settings
10	GentleBreeze™ Drying System w/ Advanced Moisture Sensing	5	High, Medium, Low, Extra Low, Air Only

Design

Size (H x W)	Depth	Weight
42" x 29"	Gas: 29-1/4" Electric: 29-1/4"	Gas: 155 lbs. Electric: 152 lbs.

Matching Washers

33842

Step-Up Washers

33872 - 4.8 Cu. Ft. Capacity

Red Indicates step-up feature

7/63842

Maytag® Bravos XL®

Cycles(10)	Options(8)	Key Features
<input checked="" type="checkbox"/> Timed Dry <input type="checkbox"/> Air Fluff/No Heat <input type="checkbox"/> Auto Dry <input checked="" type="checkbox"/> Wrinkle Control <input type="checkbox"/> Sensor Dry <input checked="" type="checkbox"/> Normal <input checked="" type="checkbox"/> Delicate <input checked="" type="checkbox"/> Heavy Duty <input checked="" type="checkbox"/> Bulky <input checked="" type="checkbox"/> Small Loads <input checked="" type="checkbox"/> Sheets <input checked="" type="checkbox"/> Freshen Up <input checked="" type="checkbox"/> Auto Refresh w/ Steam <input type="checkbox"/> Towels <input type="checkbox"/> Sanitize <input type="checkbox"/> Active Wear <input type="checkbox"/> Denim <input type="checkbox"/> Custom Refresh w/ Steam	<input checked="" type="checkbox"/> Temp Level (5) <input checked="" type="checkbox"/> End of Cycle Signal (Hi/Low/Off) <input checked="" type="checkbox"/> Wrinkle Control (Wrinkle Prevent, up to 150 Min.) <input checked="" type="checkbox"/> Dryness Level (4) <input checked="" type="checkbox"/> Damp Dry Signal <input checked="" type="checkbox"/> Time Adjust (More Time/Less Time) <input checked="" type="checkbox"/> Start/Pause <input checked="" type="checkbox"/> Drum Light <input type="checkbox"/> Wrinkle Prevent w/ Steam <input type="checkbox"/> Wrinkle Prevent without Steam <input type="checkbox"/> Reduce Static <input type="checkbox"/> Steam Boost <input type="checkbox"/> Custom Refresh	<input checked="" type="checkbox"/> Reversible, Side-Swing Door <input checked="" type="checkbox"/> Maytag® Commercial Technology <input checked="" type="checkbox"/> Interior Drum Light <input checked="" type="checkbox"/> IntelliDry® Sensor <input type="checkbox"/> Auto Moisture Sensing <input checked="" type="checkbox"/> QuietSeries™ Sound Package <input checked="" type="checkbox"/> Advanced Moisture Sensing <input checked="" type="checkbox"/> Check Lint Screen Indicator <input checked="" type="checkbox"/> LCD Screen w/ Time Remaining Display <input checked="" type="checkbox"/> Enhanced Airflow Monitor <input checked="" type="checkbox"/> Direct Y-Connector Water Hook-Up <input type="checkbox"/> Smoked Glass Window

Parts & Kits

Door Reversal	LP Conversion Kit	Cord
Reversible, No Additional Kit Required	—	Gas: 110v Cord Included

Venting

2-Way (rear, bottom)

See Installation page IG 35 for details

Side/Bottom Venting ¹	Vent - Left	Vent - Right	Vent - Bottom
Gas	Not Applicable	Not Applicable	49610
Electric	Not Applicable	Not Applicable	49610

Order through Sears Parts and Services: 1-800-469-4663

Special Instructions	Warranty
	1-Year Parts, Labor

1) Internal venting kit only.



Key Features

- 7.3 Cu. Ft. Capacity
- Auto Refresh w/ Steam Cycle
- Sanitize Cycle
- Towels Cycle
- LCD Screen w/ Time Remaining
- GentleBreeze™ Drying System w/ Advanced Moisture Sensing
- DuraCushion™ Dryer Drum
- Smoked Glass Window

White 7/63872 (MGD/MEDB880BW)

X/X/14

Product Overview

Capacity	Filter	Controls	Drum Material	Dryer Rack
7.3 Cu. Ft.	Upfront	Electronic	Painted Steel	See Parts Section for Details

Dry System

Cycles	Dry Control	Temps.	Temp. Settings
11	GentleBreeze™ Drying System w/ Advanced Moisture Sensing	5	High, Medium, Low, Extra Low, Air Only

Design

Size (H x W)	Depth	Weight
45-1/2" x 29"	Gas: 29-1/4" Electric: 29-1/4"	Gas: 161 lbs. Electric: 158 lbs.

Matching Washers

33872

Step-Up Washers

33892 - Sanitary w/ Oxi & Steam Cycle

Red Indicates step-up feature



Dryers

7/63872

Maytag® Bravos XL®

Cycles(11)	Options(8)	Key Features
<input checked="" type="checkbox"/> Timed Dry <input type="checkbox"/> Air Fluff/No Heat <input type="checkbox"/> Auto Dry <input checked="" type="checkbox"/> Wrinkle Control <input type="checkbox"/> Sensor Dry <input checked="" type="checkbox"/> Normal <input checked="" type="checkbox"/> Delicate <input checked="" type="checkbox"/> Heavy Duty <input checked="" type="checkbox"/> Bulky <input checked="" type="checkbox"/> Small Loads <input checked="" type="checkbox"/> Sheets <input type="checkbox"/> Freshen Up <input checked="" type="checkbox"/> Auto Refresh w/ Steam <input checked="" type="checkbox"/> Towels <input checked="" type="checkbox"/> Sanitize <input type="checkbox"/> Active Wear <input type="checkbox"/> Denim <input type="checkbox"/> Custom Refresh w/ Steam	<input checked="" type="checkbox"/> Temp Level (5) <input checked="" type="checkbox"/> End of Cycle Signal (Hi/Low/Off) <input checked="" type="checkbox"/> Wrinkle Control (Wrinkle Prevent, up to 150 Min.) <input checked="" type="checkbox"/> Dryness Level (5) <input checked="" type="checkbox"/> Damp Dry Signal <input checked="" type="checkbox"/> Time Adjust (More Time/Less Time) <input checked="" type="checkbox"/> Start/Pause <input checked="" type="checkbox"/> Drum Light <input type="checkbox"/> Wrinkle Prevent w/ Steam <input type="checkbox"/> Wrinkle Prevent without Steam <input type="checkbox"/> Reduce Static <input type="checkbox"/> Steam Boost <input type="checkbox"/> Custom Refresh	<input checked="" type="checkbox"/> Reversible, Side-Swing Door <input checked="" type="checkbox"/> Maytag® Commercial Technology <input checked="" type="checkbox"/> Interior Drum Light <input checked="" type="checkbox"/> IntelliDry® Sensor <input type="checkbox"/> Auto Moisture Sensing <input checked="" type="checkbox"/> QuietSeries™ Sound Package <input checked="" type="checkbox"/> Advanced Moisture Sensing <input checked="" type="checkbox"/> Check Lint Screen Indicator <input checked="" type="checkbox"/> LCD Screen w/ Time Remaining Display <input checked="" type="checkbox"/> Enhanced Airflow Monitor <input checked="" type="checkbox"/> Direct Y-Connector Water Hook-Up <input checked="" type="checkbox"/> Smoked Glass Window

Parts & Kits

Door Reversal	LP Conversion Kit	Cord
Reversible, No Additional Kit Required	—	Gas: 110v Cord Included

Venting

2-Way (rear, bottom)

See Installation page IG 35 for details

Side/Bottom Venting ¹	Vent - Left	Vent - Right	Vent - Bottom
Gas	Not Applicable	Not Applicable	49610
Electric	Not Applicable	Not Applicable	49610

Order through Sears Parts and Services: 1-800-469-4663

Special Instructions	Warranty
	1-Year Parts, Labor

1) Internal venting kit only.



Key Features

- 7.3 Cu. Ft. Capacity
- Auto and **Custom Refresh** w/ Steam Cycles
- **Wrinkle Prevent** w/ Steam Option
- **Steam Boost** Option
- LCD Screen w/ Time Remaining
- GentleBreeze™ Drying System w/ Advanced Moisture Sensing
- **Reduce Static** Option
- **Denim and Active Wear** Cycles

Chrome Shadow 7/63891 (MGD/MEDB980BG)

White 7/63892 (MGD/MEDB980BW)

X/X/14

Product Overview

Capacity	Filter	Controls	Drum Material	Dryer Rack
7.3 Cu. Ft.	Upfront	Electronic	Painted Steel	See Parts Section for Details

Dry System

Cycles	Dry Control	Temps.	Temp. Settings
14	GentleBreeze™ Drying System w/ Advanced Moisture Sensing	5	High, Medium, Low, Extra Low, Air Only

Design

Size (H x W)	Depth	Weight
45-1/2" x 29"	Gas: 29-1/4" Electric: 29-1/4"	Gas: 161 lbs. Electric: 158 lbs.

Matching Washers

33891/2

Step-Up Washers

Not Applicable

Red Indicates step-up feature



Dryers

Cycles(14)	Options(13)	Key Features
<input checked="" type="checkbox"/> Timed Dry <input type="checkbox"/> Air Fluff/No Heat <input type="checkbox"/> Auto Dry <input checked="" type="checkbox"/> Wrinkle Control <input type="checkbox"/> Sensor Dry <input checked="" type="checkbox"/> Normal <input checked="" type="checkbox"/> Delicate <input checked="" type="checkbox"/> Heavy Duty <input checked="" type="checkbox"/> Bulky <input checked="" type="checkbox"/> Small Loads <input checked="" type="checkbox"/> Sheets <input type="checkbox"/> Freshen Up <input checked="" type="checkbox"/> Auto Refresh w/ Steam <input checked="" type="checkbox"/> Towels <input checked="" type="checkbox"/> Sanitize <input checked="" type="checkbox"/> Active Wear <input checked="" type="checkbox"/> Denim <input checked="" type="checkbox"/> Custom Refresh w/ Steam	<input checked="" type="checkbox"/> Temp Level (5) <input checked="" type="checkbox"/> End of Cycle Signal (Hi/Low/Off) <input checked="" type="checkbox"/> Wrinkle Control (Wrinkle Prevent, up to 150 Min. w/ Steam) <input checked="" type="checkbox"/> Dryness Level (5) <input checked="" type="checkbox"/> Damp Dry Signal <input checked="" type="checkbox"/> Time Adjust (More Time/Less Time) <input checked="" type="checkbox"/> Start/Pause <input checked="" type="checkbox"/> Drum Light <input checked="" type="checkbox"/> Wrinkle Prevent w/ Steam <input checked="" type="checkbox"/> Wrinkle Prevent without Steam <input checked="" type="checkbox"/> Reduce Static <input checked="" type="checkbox"/> Steam Boost <input checked="" type="checkbox"/> Custom Refresh (5)	<input checked="" type="checkbox"/> Reversible, Side-Swing Door <input checked="" type="checkbox"/> Maytag® Commercial Technology <input checked="" type="checkbox"/> Interior Drum Light <input checked="" type="checkbox"/> IntelliDry® Sensor <input type="checkbox"/> Auto Moisture Sensing <input checked="" type="checkbox"/> QuietSeries™ Sound Package <input checked="" type="checkbox"/> Advanced Moisture Sensing <input checked="" type="checkbox"/> Check Lint Screen Indicator <input checked="" type="checkbox"/> LCD Screen w/ Time Remaining Display <input checked="" type="checkbox"/> Enhanced Airflow Monitor <input checked="" type="checkbox"/> Direct Y-Connector Water Hook-Up <input checked="" type="checkbox"/> Smoked Glass Window

Parts & Kits

Door Reversal	LP Conversion Kit	Cord
Reversible, No Additional Kit Required	—	Gas: 110v Cord Included

Venting

2-Way (rear, bottom)

See Installation page IG 35 for details

Side/Bottom Venting ¹	Vent - Left	Vent - Right	Vent - Bottom
Gas	Not Applicable	Not Applicable	49610
Electric	Not Applicable	Not Applicable	49610

Order through Sears Parts and Services: 1-800-469-4663

Special Instructions

Warranty

1-Year Parts, Labor

1) Internal venting kit only.

Allergen Cycle

- This washer cycle has been proven to eliminate 95 percent of common allergens from fabric, such as dust mites and pet dander.

Cold Wash Cycle

- This cycle helps power out tough stains, using cold water and extra cleaning action to provide energy savings and excellent fabric care.

Fountain™ Impeller

- The Fountain™ impeller repeatedly scoops up water and detergent from the bottom of the washer and moves it upwards through clothing.

IntelliClean™ Impeller

- Available in high-efficiency, top-load washers, the IntelliClean™ impeller wash plate has fins at the bottom to continuously move clothes through the washer. It cleans more gently than a traditional agitator and takes up less space to maximize capacity.

Maytag® Commercial Technology

- Maytag brand washers feature long-lasting, commercial-grade, corrosion-resistant springs for years of dependable use.

Optimal Dispenser Drawer

- The dispensers release detergent and other additives at just the right time for enhanced cleaning performance.

PowerSpray Technology

- Water and detergent are sprayed directly onto clothes early in the cycle to ensure that detergent is evenly distributed throughout the load.

PowerWash® Cycle

- A combination of extra cleaning action and a thorough rinse helps remove even the toughest stains.

PowerWash® System

- In conjunction with the PowerWash® cycle, this system uses the optimal dispenser drawer to help power out the toughest stains.

Sanitary Cycle with Oxi and Steam

- This cycle uses steam and an oxi additive during the wash cycle to kill 99.9% of household bacteria.

Sanitize with Oxi

- Washers with this cycle add oxi at the right time to sanitize and remove 99.9% of household bacteria.

SmoothClose™ Lid

- Maytag brand's SmoothClose™ lid hinge design closes the washer lid slowly, helping with loading and unloading.

Stainless Steel Wash Basket

- The stainless steel wash basket is durable and adds a polished, premium look and feel.

Maytag® Matching Dryer Glossary

Advanced Moisture Sensing

- Three sensors monitor temperatures and moisture levels. This precision results in even drying, eliminates over drying and saves money.

Auto Refresh Cycle with Steam

- A fine mist is sprayed into the heated dryer drum as clothes tumble, creating steam to help refresh wrinkled clothing. This cycle ends with a brief cool down period.

Direct Y-Connector Water Hook-Up

- A Y-connector delivers water from the cold water inlet directly to the dryer. It eliminates the need to fill a reservoir in dryers that feature steam-enhanced cycles.

Enhanced Airflow Monitor

- This airflow monitor automatically checks venting performance to maximize results at the start of every cycle, then provides a convenient visual display.

GentleBreeze™ Drying System

- The GentleBreeze™ Drying System with the IntelliDry® sensor quickly and efficiently dries clothing with consistent results. As clothes move around the dryer drum, air moves in a counter-clockwise loop to thoroughly dry a 16-lb load for even drying.

IntelliDry® Sensor

- This sensor measures moisture levels with two moisture strips and automatically stops the dryer when clothes are dry. This saves time and helps minimize the risk of over drying and shrinking.

Maytag® Commercial Technology

- Maytag brand dryers feature long-lasting, commercial-grade components for years of dependable use, including a high-performance motor, premium drum rollers and a 5-rib dryer belt.

Reduce Static Option

- A fine mist is sprayed into the heated dryer drum at the end of the cycle to create steam and help reduce static in the load.

X/X/14



Sanitize Cycle

- This cycle removes 99.9% of three common bacteria from clothing and fabrics.

Wrinkle Control Option

- Designed to dry clothes such as knits and permanent press fabrics, this option helps minimize wrinkles by providing a longer, unheated tumbling period at the end of the cycle.

Wrinkle Shield with Steam Option

- This option provides intermittent tumbling and bursts of steam at the end of the cycle to help reduce wrinkles.