

**GENERAL NOTED**

- A. DO NOT SCALE THE DRAWINGS
- B. GENERAL CONTRACTOR TO VERIFY FIELD CONDITIONS PRIOR TO COMMENCEMENT OF EACH PORTION OF THE WORK.
- C. THE CONTRACT DOCUMENT ARE COMPLEMENTARY: WITH IS REQUIRED BY ONE IS AS BINDING AS IF REQUIRED BY ALL. THE CONTRACTOR SHALL COORDINATE ALL PORTIONS OF THE WORK AS DESCRIBED IN THE CONTRACT DOCUMENTS. NOTIFY THE COR FOR RESOLUTION OF ALL DISCREPANCIES PRIOR TO CONSTRUCTION.
- D. UNLESS OTHERWISE INDICATED, PLAN DIMENSIONS ARE TO COLUMN GRID ON CENTERLINES, NOMINAL SURFACE OF MASONRY, FACE OF STUDS AND FACE OF CONCRETE WALLS.
- E. "FLOOR LINE" REFERS TO TOP OF CONCRETE SLABS. FINISH FLOORING IS INSTALLED ABOVE THE FLOOR LINE. FOR DEPRESSED FLOORS AND CURBS, SEE STRUCTURAL DRAWINGS.
- F. REPETITIVE FEATURES ARE NOT DRAWN IN THEIR ENTIRETY AND SHALL BE COMPLETELY PROVIDED AS IF DRAWN IN FULL.
- G. WHERE A DOOR IS LOCATED NEAR CORNER OF ROOM AND IS NOT LOCATED BY DIMENSION ON PLAN OR DETAILS, DIMENSION SHALL BE 76 (3") FROM FACE OF STUD (WALL) TO FACE OF ROUGH OPENING. DIMENSION SHALL BE 153 (6") FROM FACE OF WALL TO EDGE OF ROUGH OPENING AT CONCRETE WALLS.
- H. AT SECURITY WALLS, FULL HEIGHT PARTITIONS SHALL BE SEALED BOTH SIDES WITH ACOUSTIC SEALANT, TOP, BOTTOM, INTERSECTION, DOOR FRAMES, GLAZED OPENING FRAMES, AND ALL OTHER PENETRATIONS.
- I. LINE OF EXISTING GRADES, AS SHOWN ON THE BUILDING ELEVATIONS AND SECTIONS ARE APPROXIMATE.
- J. VERIFY ALL ROUGH-IN DIMENSIONS FOR EQUIPMENT PROVIDED IN THIS CONTRACT, OR BY OTHERS.
- K. REFER TO ARCHITECTURAL, STRUCTURAL, MECHANICAL, ELECTRICAL AND OTHER CATEGORIES OR DRAWINGS FOR ADDITIONAL NOTES.
- L. VERIFY SIZE/LOCATION/FINISH/FIRE-RATING, ETC. AND PROVIDE COMPLETE ALL REQUIRED OPENINGS THROUGH FLOORS AND WALLS, ACCESS DOORS, FURRING, CURBS, ANCHORS AND INSERTS. PROVIDE ALL BASES AND BLOCKING REQUIRED FOR ACCESSORIES, MECHANICAL, ELECTRICAL AND OTHER EQUIPMENT.
- M. WALL TYPES WITH UL DESIGN NO. S SHALL BE CONSTRUCTED TO UL STANDARDS. PRODUCTS USED SHALL BEAR UL CLASSIFICATION WHERE REQUIRED BY THE UL DESIGN
- N. ALL PENETRATIONS AND OPENINGS SHALL MEET WALL ASSEMBLY FIRE RATINGS.
- O. REFER TO FINISH SCHEDULES AND COLOR LISTS FOR WALL FINISH DESIGNATIONS.
- P. REFER TO 11/A-501 FOR CONDITIONS WHERE FURRING CHANNEL & GYPSUM BOARD SPAN OVER CONCRETE PANEL JOINTS.
- Q. FOR AT/FP BRACING REQUIREMENTS, SEE GENERAL STRUCTURAL NOTES & PROJECT SPECIFICATIONS.
- R. SEE STRUCTURAL GENERAL NOTES FOR MINIMUM STUD DEPTH, THICKNESS, FLANGE WIDTH AND SPACING.
- S. AT ALL PENETRATIONS AND INTERSECTIONS OF FIRE-RATED PARTITIONS, PROVIDE FIRE SEALANT AND / OR FIRESTOPPING TO MAINTAIN CONTINUITY OF PARTITION RATING.

LEGEND:


**Impression  
design**

ARCHITECTURE PLAN

OWNER	STAR FIRE
ARCHITECT	HOR KIMHORNG

DRAWING TITLE :  
GENERAL NOTE

DATE: 13/03/2016      SCALE: N/A

DRAWING NO: AS-A-06