



ROUT ELECTRICAL FOR FLUORESCENT LIGHT BANKS IN UPPER PANELS (NOT SHOWN) STRAIGHT DOWN TO LOWER PANELS AND OVER TO MONITOR ENCLOSURE - BACK LIT SIGNS AND ATTACHMENT T.B.D. AS OF 2/21/98

ALL UPPER PANELS TO BE BOLTED TOGETHER AND TO LOWER PANELS WITH 2" X 1/4"/20 CARRIAGE BOLTS AND THREADED INSERTS

ROUT ALL ELECTRICAL FROM LOW VOLTAGE DOWN LIGHTS IN HEADERS THRU PANELS TO POWER CONVERTER LOCATED BEHIND MONITOR WALL

PROVIDE SMALL ACCESS HOLE IN PANEL 31 FOR ELECTRICAL FROM MAIN WALL PANELS

PROVIDE BLACK CANVAS COVER FOR TOP OF MONITOR ENCLOSURE - PROVIDE GROMMETS IN COVER AND HOOKS IN WALL PANELS FOR ATTACHMENT

3/4" PLYWOOD PLATFORM AT APPROPRIATE HEIGHT TO SUPPORT MONITOR WALL

ENTIRE MONITOR WALL ENCLOSURE TO BE BOLTED TOGETHER WITH 2" X 1/4"/20 CARRIAGE BOLTS AND WING NUTS - LOCATE SPANNING HEADERS WITH 2cm DIA. FLUTED DOVELS FOR ADDED SUPPORT

3 X 3 RENTED MONITOR WALL

ROUT ALL ELECTRICAL FROM LOW VOLTAGE DOWN LIGHTS IN HEADERS THRU PANELS TO POWER CONVERTER LOCATED BEHIND MONITOR WALL

REMOVABLE PANELS WITH DOWN LIGHTING ON ALL MAIN PANELS FOR EASE IN ELECTRICAL ROUTING

BOLT ALL LOWER PANELS TOGETHER WITH 2" X 1/4"/20 CARRIAGE BOLTS AND THREADED INSERTS

EXPLODED ASSEMBLY

NOT TO SCALE